

## General Accessories

### Light Kits



Magnet mount not included - must be ordered separately.



### Fluorescent Light Kit & Accessories

- Light kits are offered in 18", 24" and 48" widths.
- CSA and UL component recognized.
- Operating voltage 115 AC 60Hz
- Features a manually operated switch, 115V convenience outlet, durable plastic lens, and 6 foot power cord (without plug).
- Can mount into light mounting channel, bolt through enclosure or by using magnet strip (available separately - see chart below.)
- Magnet mount can be used with mild steel enclosures only.
- Remote door switch available separately for automatic activation.
- Finished in white.
- Use standard 18", 24" or 48" T8 fluorescent bulb (not included)

Part No.	Description
<b>FLK18T8<sup>1</sup></b>	18" Fluorescent Light Kit
<b>FLK24T8<sup>1</sup></b>	24" Fluorescent Light Kit
<b>FLK48T8<sup>1</sup></b>	48" Fluorescent Light Kit
<b>FLK18MM</b>	Magnet mount for 18" and 24" kit
<b>FLK48MM</b>	Magnet mount for 48" light kit

<sup>1</sup> T8 fluorescent bulb not included



### LED light kits

- Available in 9", 17.5", 26", 34.5" and 38.5" lengths
- Operating voltage 100/240V AC 50/60Hz Operating temperature -20 C to + 50 C
- Long lamp life 60,000 hours in warm white color temperature
- No remote power supplies as unit comes with its own integral LED drivers
- Hard wired via multiple knockouts in light weight extruded Aluminum frame finished white with manual operated switch
- Hinged glass diffuser allows easy access to replaceable LED module
- Remote door switch available separately for automatic activation

Part No.	Description	Number LED	
		Modules	Energy Use
<b>FLK5LED</b>	9" LED Light Kit	1.00	4.4 w
<b>FLK7LED</b>	17.5" LED Light Kit	2.00	7.2 w
<b>FLK10LED</b>	26" LED Light Kit	3.00	9.8 w
<b>FLK15LED</b>	34.5" LED Light Kit	4.00	15.0 w
<b>FLK17LED</b>	38.5" LED Light Kit	5.00	17.0 w



FDS1

FLKDS



### Remote Door Switch

- Permits convenient door activated on-off function of lights & air conditioners.
- Can be wired normally open or normally closed.
- 115/230 V AC

Part No.	For use with
<b>FLKDS</b>	1418, 1422, 1447, 2UD, UHD
<b>FDS1</b>	Eclipse, HME